



<b>Product Code</b>	SHA-CHR-1150EF
<b>Description</b>	Slide Rail (φ19mm & 600mm) with Multifunction Hand Shower (HSH-1939) with 1.5M Long Flexible Hose and soap dish
<b>Flow Rate</b>	Normal - 16.51 LPM @ 3 bar Soft - 14.07 LPM @ 3 bar Massage - 10.42 LPM @ 3 bar
<b>Flow regulator</b>	By using flow regulators + Brass Housing (Product should be ordered with suffix as GA-6.0 LPM, GB-8.0 LPM, & GC-12.0 LPM @ 4.0 Bar pressure) one can regulate the flow rate.
<b>Recommended Water Pressure</b>	1.0 Bar - 3.0 Bar
<b>Spray Modes</b>	Normal, Soft and Massage functions
<b>Material Composition Specification in Percentage</b>	<p><b>Brass Rod as per IS:319-1989</b> Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)</p> <p><b>Brass Pipe as per IS:407-1996</b> Cu (62.0-65.0), Pb (0.0-0.3), Fe (0.0-0.01), Total Impurity (0.0-0.6), Zn (Remainder)</p> <p><b>ABS Specification</b> Specific Gravity g/cm<sup>2</sup> (1.06-1.10), Melt Mass Flow Rate g/10 min. (20-26), Rockwell Hardness (95-115), DTUL @ 66 psi /0.45 MPa 0C (78-102)</p>
<b>Finish</b>	Salt Spray (350 hrs + Validated)
<b>Available Colour Finishing</b>	CHROME (CHR)
DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.	