




Product Code	OHS-CHR-1709
Description	Single Function 105mm dia Round Shape Overhead Shower with Air Effect
Flow Rate	12.12 LPM @ 3 bar
Flow regulator	By using flow regulators + Brass Housing (Product should be ordered with suffix as GA-6.0 LPM, GB-8.0 LPM & GC-12.0 LPM @ 4.0 Bar pressure) one can regulate the flow rate.
Recommended Water Pressure	1.0 Bar - 3.0 Bar
Mount Type	Wall Mounting
Spray Modes	Single Function
Material Composition Specification in Percentage	Brass Rod as per IS:319-1989 Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder) ABS Specification Specific Gravity g/cm ² (1.06-1.10), Melt Mass Flow Rate g/10 min. (20-26), Rockwell Hardness (95-115), DTUL @ 66 psi /0.45 MPa 0C (78-102)
Technology	Unique Air Technology - Air is mixed in the water through a built-in air mixer which is a part of the shower. This leads to lighter voluminous drops which reduce water consumption by 30% and also assuring a soft and refreshing shower Advanced Rubit - Lime scale deposits stick to the shower face can be easily rubbed off by hand or flannel.
Finish	Salt Spray (350 hrs + Validated) Adhesion (Pass)
Available Finishing	CHROME (CHR)
DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.	