







FFIvi

TOP VIEW

340





IGQUOF BATH+LIGHT

ONS-WHT-10955P180UFSM
Jaquar
White
Back To Wall WC
Ceramic - Vitreous China
360x575x410 mm
275X340 mm
25.5 Kg
27.5 kg
550x370x420mm
Vertical
Internal diameter of inlet hole dia. Ø 58 ± 3 mm
External diameter of outlet hole dia. Ø 100 ± 5 mm
Vertical distance between the Floor and the centre line of the waste outlet hole ≤ 180 mm
Rimless design with slim seat cover, Dual Flush - 3/6 LPF, Anti germ glaze.
ONS-WHT-10105
ZPS-SNS-FB02
ZPS-WHT-GK01
JCS-WHT-2400WS,JCS-WHT-2400,JCS-WHT-2400P,JCS-WHT-2400S,JCS-WHT-2431, JCS-WHT-2431P,JCS-WHT-2431S.

CARE AND CLEANING GUIDELINES

- vitreous china sanitaryware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter
- The product is heavy and it is recommended that two persons hold it while it is being fixed.
- , Carefully inspect the new product for damage before installation. Recommended to inspect the sanitaryware with wooden Hammer.
- Risk of product damage. Over tightening may cause breakage or chipping of vitreous china. Recommended to use hard rubber & nylon spacer in between ceramic & metal fixtures.
- Risk of external leakage. Do not lift or rock the bowl after placement.
- Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.
- Do not allow cleaners to sit or soak on the product.
- use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad
- wipe surfaces clean and rinse completely with water immediately after applying cleaners.
- Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.
- $_{ extsf{h}}$ Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.
- Recommended to use Genuine Accessories.

QUALITY MANAGEMENT SYSTEM - ISO 9001



"DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. All dimensions are in mm (Tolerance ± 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice. # For Installation Refer Actual Product, Last modified on 26 December 2025