




GENERAL INFORMATION

Product Code	ITS-WHT-15955P180PP
Brand	Jaquar
Colour	White
Type	Back To Wall WC - P TRAP
Material	Ceramic-Vitreous China (VC)

PRODUCT SPECIFICATION

Product Dimension	370x580x430 mm
Bowl Opening (Inner Dimension)	260x335 mm
Product Net Weight	29.0 kg.
Product Gross Weight	32.5 kg
Packaging Dimension	600x440x450 mm
Outlet	Horizontal
Trap Distance	P Trap - 180 mm
Inlet And Outlet Hole Dimension	Internal diameter of inlet hole dia. $\varnothing 58 \pm 3$ mm External diameter of outlet hole dia. $\varnothing 100 \pm 5$ mm

PRODUCT FEATURES

Product Features	4. Dual Flush-3/6 LPF Intelligent Seat with following features: 1. Adjustable seat temperature - 33/37°C 2. Adjustable water temperature - 35/38°C 3. Adjustable air temperature - 33/38/43°C 4. Anti-bacterial seat/nozzle/ceramic 5. LED night light 6. Air dryer 7. Front & rear wash nozzle 8. Adjustable water pressure 9. Instant heating technology 10. Self-cleaning 11. Water massage cleaning
------------------	--

ACCESSORIES PROVIDED

Electronic PP Seat cover	ITS-WHT-89107
Inlet outlet Gasket	ZPS-WHT-GK01
Fixing kit	ZPS-SNS-FB02

CARE AND CLEANING GUIDELINES

Concealed cistern	JCS-WHT-2400WS, JCS-WHT-2400, JCS-WHT-2400P, JCS-WHT-2400S, JCS-WHT-2431, JCS-WHT-2431P, JCS-WHT-2431S.
-------------------	---

CARE AND CLEANING GUIDELINES

- ☑ Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter.
- ☑ The product is heavy and it is recommended that two persons hold it while it is being fixed.
- ☑ Carefully inspect the new product for damage before installation. Recommended to inspect the sanitaryware with wooden Hammer.
- ☑ Risk of product damage. Over tightening may cause breakage or chipping of vitreous china. Recommended to use hard rubber & nylon spacer in between ceramic & metal fixtures.
- ☑ Risk of external leakage. Do not lift or rock the bowl after placement.
- ☑ Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.
- ☑ Do not allow cleaners to sit or soak on the product.
- ☑ Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.
- ☑ Wipe surfaces clean and rinse completely with water immediately after applying cleaners.
- ☑ Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.
- ☑ Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.
- ☑ Recommended to use Genuine Accessories.

QUALITY MANAGEMENT SYSTEM - ISO 9001



DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. All dimensions are in mm (Tolerance ± 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice.

For Installation Refer Actual Product. Last modified on September 2026.