

SLS-WHT-6951JPPSM

SPECIFICATION DATA SHEET

DRODUCT DETAILS

PRODUCT DETAILS							
Manufacturer :	Jaquar	Туре:	Wall hung WC (water closet)				
Range	Solo	Flush valves	Regular, Dual & I Flush advantages				
Colour:	White	Material:	Ceramic - Vitreous China				
Outlet	Vertical	BOM doc.NO.	JSW/12/2017/0123				
	T						

Technical Details: Internal diameter of inlet hole Ø 58 +2 -1 mm

External diameter of outlet hole Ø 100 +5 -2 mm


ARTICLE NAME: WALL HUNG WC









TECHNICAL DIMENSIONS







BACK VIEW

ALL DIMENSIONS ARE IN MM. (TOLERANCE ± 5 MM)

PRODUCT DIMENSIONS				USP					
Length (mm)	Width (mm)	Height (mm)	Net weight (kg)						
365	515	390	22.90	Box rim with In-build jet , slim seat cove , Anti germ glaze					
ACCESSORIES PROVIDED									
PP soft Close Slim seat cover				SLS-WHT-6103SM					
Inlet & Outlet gasket				ZPS-WHT-GK01					
	Bide	et Pipe		ZPS-WHT-5601					
ACCESSORIES RECOMMENDED									
Rag bolt				ZPS-MST-RB07					
Concealed cistern model no				JCS-WHT-2400S,2400FS,2400WS					





CARE AND CLEANING GUIDELINES

- * Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter.
- \bigstar The product is heavy and it is recommended that two persons hold it while it is being fixed.
- \bigstar Carefully inspect the new product for damage before installation.
- \bigstar Risk of product damage. Over tightening may cause breakage or chipping of vitreous china.
- ★ Risk of external leakage. Do not lift or rock the bowl after placement.
- ★ Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.
- \bigstar Do not allow cleaners to sit or soak on the product.
- ★ Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.
- ★ Wipe surfaces clean and rinse completely with water immediately after applying cleaners.
- ★ Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.

 $m{\star}$ Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.

CERTIFICATION

Compliance: IS 2556.2:2004, IS 2556.1:1994, EN 997:2012+A1/CE
All technical dimensions are in accordance to British standards, Bureau of Indian Standards





PACKAGING DETAIL LOADING PALLET DETAIL Length (mm) Width (mm) Height (mm) Gross Weight(kg) Length (mm) Width (mm) Height (mm) No of pieces on pallet 445 420 1140 1140 2285 535 26.00 16





JP J									
Prepared By		Controlled By	Verified By	Verified By		Approved By			
Designer		Quality control	Product Manager		Sanitaryware H	lead			
Date									
Revision/Version	1		Plotter Updated on	Month	10-Jul	Year	2018		
Date	1	Quanty Control			,		2018		