



Product Code	PRS-STL-033EFP
Description	Exposed Foot Operated Non-concussive Valve for Pressmatic Basin Taps Only with Plug (Table Mounted Model) with Two 900 & 1200mm Long Braided Hoses with 15mm Nuts
Recommended Water Pressure	0.2 Bar - 4.0 Bar
Material Composition Specification in Percentage	<p>Brass Ingots as per IS:1264-1997 Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total Impurity (0.0-2.0), Zn (Remainder)</p> <p>Brass Rod as per IS:319-1989 Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)</p> <p>S.S Sheets as per AISI : 304 Ni (8.0-11.0), Ch (18.0-20.0), Mn (0.0-0.2), Ca (0.0-0.08), Fe (Remainder)</p>
Cartridge Specification	<p>Fittings : Hydro-mechanical activation, light manual pressure and with automatic timed closure</p> <p>Actuation time : 7 Sec (average)</p> <p>Maximum water temperature: 70°C</p> <p>Life Cycle EN 816: 210,000 cycles (with static pressure 4±0.5 bar) cartridge complies with this requirement.</p>
Water Tightness	16 bar (Pass)
Finish	<p>Plating: Nickel-10.0 micron Chromium-0.3 micron</p> <p>Salt Spray (500 hrs + Validated)</p> <p>Adhesion (Pass)</p>
Available Colour Finishing	Satinless Steel (STL)
<p>DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. Jaquar reserves the right to make the necessary amendments at any time without prior notice.</p>	