





Product Code	LAG-CHR-91121K
Description	Exposed Parts of Floor Mounted Single Lever Bath Mixer with Provision for Hand Shower, without Hand Shower &
	Shower Hose (Compatible with ALD-121)
Flow Rate	17.53 LPM @ 3 bar
Flow regulator	By using flow regulators (Product should be ordered with suffix as G-2.5 LPM, GA-6.0 LPM, GB-8.0 LPM, GC-13.0
	LPM, GD-3.8 LPM & GE-1.3 LPM @ 3.0 Bar pressure) one can regulate the flow rate.
Recommended	1 O Day 5 Day
Water Pressure	1.0 Bar - 5 Bar
Brass Specification in Percentage	Brass Ingots as per IS:1264-1997
	Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total Impurity (0.0-2.0), Zn
	(Remainder)
	Brass Rod as per IS:319-1989
	Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)
	Brass Pipe as per IS:407-1996
	Cu (62.0-65.0), Pb (0.0-0.3), Fe (0.0-0.01), Total Impurity (0.0-0.6), Zn (Remainder)
Cartridge Specification	NSF-61 Approved Cartridge with Temperature Limiter
	Cartridge with Brass Spindle
	Life Cycle EN 817: 70,000 cycles (Standard)
	- 2.1 LAC Cycles as per EN 817*
	- 10.5 LAC Cycles (ON/OFF)*
Water Tightness	16 bar (Pass)
Pressure Resistance	25 bar (Pass)
Finish	Plating: Nickel-10.0 micron Chromium-0.3 micron
	Salt Spray (500 hrs + Validated)
	Adhesion (Pass)
Available Single	
Colour Finishing	Black Chrome (BCH), Black Matt (BLM), Gold Matt-PVD (GMP), Gold Bright-PVD (GBP)
Available Dual Colour	
Finishing	Black Matt & Black Chrome (BBC), Gold Matt-PVD & Gold Bright-PVD (GMG), Black Matt & Gold Matt-PVD (BGM)
(First Colour for Body	
& Second for Lever)	

^{*} As per in-house testing done on automatic life cycle testing machine made by Giussain, Italy

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.