



<b>Product Code</b>	OHS-CHR-1779
<b>Description</b>	Multifunction 120mm Round Shape Overhead Shower with Rain, Soft, Massage & Cascade Spray
<b>Flow Rate</b>	“Normal - 16.64 LPM @ 3 bar Soft - 11.56 LPM @ 3 bar Massage - 12.83 LPM @ 3 bar Cascade - 12.51 LPM @ 3 bar”
<b>Flow regulator</b>	By using flow regulators + Brass Housing (Product should be ordered with suffix as GA-6.0 LPM, GB-8.0 LPM, & GC-12.0 LPM @ 3.0 Bar pressure) one can regulate the flow rate.
<b>Recommended Water Pressure</b>	1.0 Bar - 3.0 Bar
<b>Mount Type</b>	Wall Mounting
<b>Spray Modes</b>	Normal, Soft, Massage and Cascade functions
<b>Material Composition Specification in Percentage</b>	<p><b>“Brass Rod as per IS:319-1989</b> Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)</p> <p><b>ABS Specification</b> Specific Gravity g/cm<sup>2</sup> (1.06-1.10), Melt Mass Flow Rate g/10 min. (20-26), Rockwell Hardness (95-115), DTUL @ 66 psi /0.45 MPa OC (78-102)”</p>
<b>Technology</b>	<p><b>“Advanced Rubit</b> - Lime scale deposits stick to the shower face can be easily rubbed off by hand or flannel.</p> <p><b>Click Position System</b> - One can feel and hear the click while changing the function of the shower sprays.”</p>
<b>Finish</b>	“Salt Spray (350 hrs + Validated) Adhesion (Pass)”
<b>Available Finishing</b>	CHROME (CHR)
<p>DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.</p>	